

2.1// BS 5163 FLANGED RESILIENT NRS GATE VALVE

(SKYZ45X), PN10/16


FEATURES

Connection Ends: Flange to BS EN 1092-2:1997

Working Pressure: PN10/16

Temperature Range: 0°C - 80°C

Coating: Fusion Bonded Epoxy Coating in accordance with ANSI/AWWA C550



MATERIAL SPECIFICATIONS

|| = Other Options

No.	Part Name	Material	No.	Part Name	Material
1	Valve Body	EN-GJS-450-10	10	Flat Washer	CS Zinc Plated SS304, SS316,
2	Resilient Wedge Disc	EN-GJS-450-10+EPDM	11	Ring Wiper	NBR EPDM
3	Stem	Stainless Steel SS304, SS316, SS420, SS431	12	Bolt	CS Zinc Plated SS304, SS316,
4	Bolt	CS Zinc Plated SS304, SS316,	13	Flat Washer	CS Zinc Plated SS304, SS316,
5	Bonnet	EN-GJS-450-10	14	O-Ring	NBR EPDM
6	O-Ring	NBR EPDM	15	Thrust Washer	Brass HPb59-1 (Type A) N/A (Type B)
7	Gland	EN-GJS-450-10	16	Bonnet Gasket	EPDM NBR
8	Handwheel	EN-GJS-450-10 Pressed Steel	17	Wedge Nut	Brass HPb59-1 Bronze ZQSn5-5-5
9	Bolt	CS Zinc Plated SS304, SS316,			

Note: For special material request other than standard specification, please indicate clearly on the inquiry or order list.